

Emisor:

Enviar a:

**PIENSA APPLIED TECHNOLOGIES S.A.**

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –  
Quilicura – Santiago  
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

**PewiSYS materIAl handling bv**

Kalkoenweg 40 3851 SC ERMELO  
Países Bajos

Please provide Certificate of Origin

Payment terms: 100% before transport

Technical notes:

- Conveyor must withstand unevenness of upto +/- 6° between floor and truck

- Conveyor is specified for cases with a base LxW between 300x200 and 700x600, traveling with its short side leading

Importes visualizados en Euros

Descripción	IVA	P.U.	Cant.	Dto.	Base imp.
pewiFLEX™ impact unit 760	0%	1.769,00	1	50%	884,50
pewiFLEX™, powered flexible roller conveyor Type: PEW 760/19.200/HD Roller Length: 760 mm Extended length: 19,2 meter Compact length: approx.. 8 meter Roller diameter: 50 mm, steel plated zinc Pitch: 130 mm Castor dimensions Ø200 x 45 mm Height top of Roller: 730-900 mm V = 6-35m/min. Dynamic capacity: 150 kg/m Power supply: 240 Volt, (3 phase), 50Hz excluding control box Including: - pre wiring and - 4 emergency panels	0%	32.560,00	1	50%	16.280,00
Roller stop with connection hooks	0%	253,00	1	50%	126,50
pewiJOINT™760	0%	335,00	1	50%	167,50

**Condiciones de pago:** Acuse de recibo

Total (Base imp). 17.458,50

Total IVA 0,00

**Tipo de pago:** Wire Transfer

**Total** 17.458,50