

Emisor:

PIENSA APPLIED TECHNOLOGIES S.A.

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –
Quilicura – Santiago
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

Enviar a:

DORNER LATIN AMERICA S DE RL CV

Domicilio Fiscal:

Carretera Nogales No. 5297, Int. 11

Col. Rancho Contento,

C.P. 45222, Zapopan, Jalisco

Mexico

De acuerdo a Propuesta Comercial QUO-28967-T4D2 Rev.0

Approval Drawing 12 Business Days, Mfg. 45 Business Days

Ex.Works México.

Importes visualizados en Dólares USA

Descripción	IVA	P.U.	Cant.	Dto.	Base imp.
<p>PATN-0000013 - Transportador de cajas ajustable 75XXX400- DeltaPack case conveyor (inside machine) - Nr. 3</p> <p>QTY 1.-32PMM04-193632SA0101N-9 / Except, with a high friction belt. 3200 Precision Move flat belt conveyor, 3.75" (95mm) wide x 19'-4.28" (5,900mm) long, .5" (12.7mm) pitch belt, with low side profile on both A and D sides. Drive shaft for side, bottom, or top mounting motor is located in position A. Includes belt return rollers but no mounting brackets. Uncrated weight = 108 lbs. (49 kg).</p> <p>QTY 1.-32MBEKA-2216 3200 & LPZ Series standard load variable speed eDrive™ bottom mounting package mounted in the A position, 22:16 pulley ratio. Uncrated weight = 13 lbs. (5.7 kg).</p> <p>QTY 1.-32M010ES423EI 3200 Series standard load 90° shaft variable speed indexing eDrive™ gearmotor, .5 Hp (.37kW), 230/460 volt, 3 phase, 6-60 Hz, 173 RPM, providing a belt speed of 21 - 208 ft/min (6.4 - 63 m/min). Order variable speed controller separately. Uncrated weight = 21 lbs. (9.6 kg).</p> <p>QTY 1.-32PMM04-193632SD0101N-9 / Except, with a high friction belt. 3200 Precision Move flat belt conveyor, 3.75" (95mm) wide x 19'-4.28" (5,900mm) long, .5" (12.7mm) pitch belt, with low side profile on both A and D sides. Drive shaft for side, bottom, or top mounting motor is located in position D. Includes belt return rollers but no mounting brackets. Uncrated weight = 108 lbs. (49 kg).</p> <p>QTY 1.-32MBEKD-2216 3200 & LPZ Series standard load variable speed eDrive™ bottom mounting package mounted in the D position, 22:16 pulley ratio. Uncrated weight = 13 lbs. (5.7 kg).</p> <p>QTY 1.-32M010ES423EI 3200 Series standard load 90° shaft variable speed indexing eDrive™ gearmotor, .5 Hp (.37kW), 230/460 volt, 3 phase, 6-60 Hz, 173 RPM, providing a belt speed of 21 - 208</p>					

ft/min (6.4 - 63 m/min). Order variable speed controller separately. Uncrated weight = 21 lbs. (9.6 kg).	0%	25.196,00	1	25%	18.897,00
QTY 1.- 75XXX400 Lower guides made of T-304 stainless steel Cal. 16 A and D side.					
QTY 1.- 75XXX400 Encoder 12mm bore, IP64, 3,000 RPM, bi-directional signal 5-26 V. Line driver out 8 pin M12 connector, cast aluminium with slotted tether.					
QTY 3.- 75XXX400 Wide Adjustable Module from 150 to 400 mm.					

Condiciones de pago:	Pago a 30 días	Total (Base imp).	18.897,00
		Total IVA	0,00
Tipo de pago:	Transferencia bancaria	Total	18.897,00