

Emisor:

Enviar a:

PIENSA APPLIED TECHNOLOGIES S.A.

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –
Quilicura – Santiago
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

DORNER LATIN AMERICA S DE RL CV

Domicilio Fiscal:

Carretera Nogales No. 5297, Int. 11

Col. Rancho Contento,

C.P. 45222, Zapopan, Jalisco

Mexico

De acuerdo a prouestas comerciales DORNER QUOTE 20210625025139/ 20210625045246/ 202107010441197

Ex Works Mexico .

Importes visualizados en Dólares USA

Descripción	IVA	P.U.	Cant.	Dto.	Base imp.
<p>PATN-0000006 - Transportador de banda SERIE 2200 22EDM10-114820A1313A5 (Qty 1) 2200 Series end drive conveyor with V-guide belt tracking, 10in (254mm) wide x 11.48ft (3499mm) long, drive shaft in position A with type 13 - bolt-on fully adjustable HDPE side profile on both sides and belt type 05, Accumulation with plastic clipper splice. Configuration includes standard drive and idler tail and mounting brackets. Uncrated weight = 77lb (35kg).</p> <p>22MBES10A-4828 (Qty 1) 2200 Series Standard Load 90 Degree bottom mount package for a end drive conveyor, mounted in the A position, 48:28 pulley ratio. Uncrated weight = 6lb (3kg).</p> <p>62M005ES423EN (Qty 1) Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 345 RPM, providing a belt speed of 35 - 207 ft/min (10.7 - 63.1 m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).</p> <p>39MFH12-1721F (Qty 3) Fixed Height Stand with fixed foot pads for up to a 12in (305mm) wide conveyor. Stand is adjustable from 17in (432mm) to 21in (533mm). Stand has a base width of 13.5in (343mm). Uncrated weight = 16lb (7kg). Required stand height is 18.7in (475mm).</p> <p>39MB-TS (Qty 3) Diagonal bracing for H style stands up to 30in (762mm) tall.</p>	0%	5.562,00	1	25%	4.171,50
<p>PATN-0000005 - Transportador de banda SERIE 7200 721M120239D01A1 (Qty 1) AquaGard™ 7200 Series end drive conveyor with V-guide belt tracking, 12" (305mm) wide x 2'-4.68" (728mm) long, drive shaft in</p>					

<p>position D, with low side frame and type 01 standard accumulation belt with plastic clipper splice. Includes recommended mounting brackets. Uncrated weight = 25 lbs. (11.3 kg).</p> <p>72MBPY12D-4822 (Qty 1) 7200 Series standard load bottom gearmotor mounting package with standard duty timing belt for a 12" (305mm) wide conveyor, mounted in the D position, 48:22 pulley ratio</p> <p>62M009PY423EN (Qty 1) AquaGard™ standard load parallel shaft variable speed VFD gearmotor,.12 Hp (.09kW), 230 volt, 3 phase, 6-60 Hz, 167 RPM. 21 - 128 ft/min (6.4 - 39 M/min) belt speed.Order variable speed controller separately. Uncrated weight = 15 lbs. (6.8 kg).</p> <p>39MFH12-2024F (Qty 1) Fixed height stand with fixed footpads for a 12" (305mm) wide conveyor. Adjustable from 20" to 24" (508mm to 610mm). Includes full width top plate. Required stand height is 22.6" (574mm). Uncrated weight = 15.12 lbs. (6.9 kg).</p>	0%	4.365,00	1	20%	3.492,00
<p>PATN-0000007 - Transportador de banda U FLEX MOVE FASR-25U (Qty 2) UHMW-PE Slide rail, white colour</p> <p>807-2694 (Qty 2) M5 Nylon set screw for slide rail, 50pcs/pk</p> <p>FATB-35 (Qty 1) T-bolt L=35mm, Steel with zinc plated, 50 pcs/pk</p> <p>FALN-M8 (Qty 1) M8 lock nut, 50pcs/pk</p> <p>FAFW-M8 (Qty 1) M8 flat washer, 50pcs/pk</p> <p>FAHB-M8X16 (Qty 1) M8 x 16 hexagon head bolt L = 16mm, 50pcs/pk</p> <p>FAVBS-80V (Qty 4) Vertical beam support bracket, 80mm (FV)</p> <p>FADBS-80VV (Qty 1) Beam Support Bracket, Direct Drive, 80mm beam, 260mm</p> <p>FATB-20 (Qty 1) T-bolt L=20mm, Steel with zinc plated, 50 pcs/pk</p> <p>FASN-M8 (Qty 1) M8 Square nut, 20x20mm, 50pcs/pk</p>					

<p>851-903 (Qty 1) Parts Assembly and Installation Manual</p> <p>FBSB-80x80 (Qty 1) Support beam, 80x80mm, 3meter/length</p> <p>FBEC-80 (Qty 1) End cap, 80x80mm support beam, 10pcs/pk, Grey</p> <p>FBFT-80D (Qty 3) Foot, for 80x80 beam, 260mmx260mm c/w connecting strip and screw</p> <p>FBCS-20X96 (Qty 1) Connecting strip for 80x80mm foot, 10pcs/pk</p> <p>FGRR-15x20 (Qty 2) Guide rail rectangular, 15x20mm, 3meter/length</p> <p>FGRC-100 (Qty 1) Rail connecting, length 100mm, with set screw, 10pcs/pk</p> <p>FGEC-30D (Qty 1) 30 Degree End Cap for FGRR-15x20, 10pcs/pk</p> <p>FGRB-40x18 (Qty 2) Guide rail bracket, 10pcs/pk</p> <p>FGRK-18x80A (Qty 2) Guide rail support, L = 80mm, 10pcs/pk</p> <p>FGRD-6B (Qty 3) Spacer for FGRB-40x## Guide rail bracket, 10pcs/pk</p> <p>FGRR-15x20HB (Qty 2) Bended aluminium guide rail for horizontal bend (inner & Outer)</p> <p>FVPC-5R (Qty 2) Standard plain chain with roller</p> <p>FVTB-A260 (Qty 2) End transfer bridge c/w roller (Casting)</p> <p>32M010ES423EN (Qty 1) Standard load E-Drive 90 Degree VFD Variable Speed gearmotor, .75 Hp (.55kw), 230/460 volt, 3 phase, 6-60 Hz, 173 RPM. Order variable speed controller separately.</p> <p>FVCB-3 (Qty 1) Conveyor beam, 3meter/length</p> <p>FVIE-A260 (Qty 1) Idler end unit (Casting). Module number 1.</p> <p>FVHB-90R700 (Qty 1)</p>					
---	--	--	--	--	--

Horizontal plain bend, 90R700mm. Module number 2.	0%	9.225,10	1	25%	6.918,83
FVHB-90R700 (Qty 1)					
Horizontal plain bend, 90R700mm. Module number 4.					
FVDD-A260-EL (Qty 1)					
Direct end drive unit without motor (L), 260mm, 0.75 in shaft. Module number 5.					

Condiciones de pago: Pago a 30 días

Total (Base imp).	14.582,33
-------------------	-----------

Tipo de pago: Transferencia bancaria

Total IVA	0,00
-----------	------

Total	14.582,33
-------	-----------