

Emisor:

**PIENSA APPLIED TECHNOLOGIES S.A.**

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –  
Quilicura – Santiago  
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

Enviar a:

**DORNER LATIN AMERICA S DE RL CV**

Domicilio Fiscal:

Carretera Nogales No. 5297, Int. 11

Col. Rancho Contento,

C.P. 45222, Zapopan, Jalisco

Mexico

Segun presupuesto QUO-29298-WOS7 REV.2

Ex works

Importes visualizados en Dólares USA

| Descripción  | IVA | P.U.     | Cant. | Dto. | Total (Base imp) |
|--|-----|----------|-------|------|------------------|
| <p>PATN-0000014 - Transportador de productos DP<br/>SERIE 2200<br/>PN-29298-WOS7-01 REV 2 (75XXXXXX) (Qty 1)<br/>2200 Series end drive conveyor with V-guide belt tracking, 12in (305mm) wide x19.68ft (6000mm) long, drive shaft in position A with type 01 - low side profile on both sides and belt type 08, High Friction with plastic clipper splice. Configuration includes standard drive and idler tail and mounting brackets. Tail corner location T3 has a keyed auxiliary shaft with a encoder similar to 980-011 except IP65, hollow bore, 12mm, 250ppr, 2meter radial cable, output signal<br/>Reference: 22EDM12-180020A0101A8-XA0K0-9 except with an encoder assy.</p> <p>22MBES12A-4828 (Qty 1)<br/>2200 Series Standard Load 90 Degree bottom mount package for a end drive conveyor, mounted in the A position, 48:28 pulley ratio. Uncrated weight = 6lb (3kg).</p> <p>62M005ES423EN (Qty 1)<br/>Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 345 RPM, providing a belt speed of 35 - 207 ft/min (10.7 - 63.1 (m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).</p> | 0%  | 6.273,00 | 1     | 25%  | 4.704,75         |

**Condiciones de pago:** Acuse de recibo

Total (Base imp). 4.704,75

**Tipo de pago:** Transferencia bancaria

Total IVA 0,00

**Total** 4.704,75