

Emisor:

PIENSA APPLIED TECHNOLOGIES S.A.

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –
Quilicura – Santiago
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

Enviar a:

DORNER LATIN AMERICA S DE RL CV

Domicilio Fiscal:

Carretera Nogales No. 5297, Int. 11

Col. Rancho Contento,

C.P. 45222, Zapopan, Jalisco

Mexico

De acuerdo a propuesta comercial 20220307111806 / 20220308063459 / 20220309063315

Ex Works México

Importes visualizados en Dólares USA

Descripción	IVA	P.U.	Cant.	Dto.	Base imp.
<p>PATN-0000535 - CNV 001</p> <p>22MDM08-0492200D010108-X000K (Qty1)</p> <p>2200 Series mid drive conveyor with V-guide belt tracking, 8in (203mm) wide x 4.92ft (1500mm) long, drive shaft in position D with type 01 - low side profile on both sides and belt type 08, High Friction with fused finger splice. Configuration includes standard discharge tail and standard infeed tail and mounting brackets. Tail corner location T4 has a keyed auxiliary shaft. Uncrated weight = 39lb (18kg).</p> <p>22M6BESD-4828 (Qty1)</p> <p>2200 Series Standard Load 90 Degree bottom mount package for a mid drive conveyor, mounted in the D position, 48:28 pulley ratio. Uncrated weight = 5lb (2kg).</p> <p>62M005ES423EN (Qty1)</p> <p>Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 345 RPM, providing a belt speed of 35 - 207 ft/min (10.7 - 63.1 m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).</p> <p>39MAH12-2436F (Qty 2)</p> <p>Adjustable Height Stand with fixed foot pads for up to a 12in (305mm) wide conveyor. Stand is adjustable from 24in (610mm) to 36in (914mm). Stand has a base width of 13.5in (343mm). Uncrated weight = 23lb (10kg). Required stand height is 30.5in (775mm).</p>	0%	3.800,00	1	25%	2.850,00
<p>PATN-0000536 - CNV 002</p> <p>22EDM18-059120D050502 (Qty 1)</p> <p>2200 Series end drive conveyor with V-guide belt tracking, 18in (457mm) wide x 5.91ft (1801mm) long, drive shaft in position D with type 05 - 1.5in (38mm) bolt-on aluminum high side profile on both sides and belt type 02, General Purpose with fused finger splice. Configuration includes standard drive and idler tail and mounting brackets. Uncrated weight = 70lb (32kg).</p> <p>22MBES18D-4828 (Qty 1)</p> <p>2200 Series Standard Load 90 Degree bottom mount package for a</p>					

<p>end drive conveyor, mounted in the D position, 48:28 pulley ratio. Uncrated weight = 6lb (3kg).</p> <p>62M005ES423EN (Qty 1) Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 345 RPM, providing a belt speed of 35 - 207 ft/min (10.7 - 63.1 m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).</p> <p>39MAH18-2436F (Qty 2) Adjustable Height Stand with fixed foot pads for a 18in (457mm) wide conveyor. Stand is adjustable from 24in (610mm) to 36in (914mm). Stand has a base width of 19.5in (495mm). Uncrated weight = 23lb (10kg). Required stand height is 30.5in (775mm).</p>	0%	4.436,00	1	25%	3.327,00
<p>PATN-0000537 - CNV 003 22EDM16-039420D010101 (Qty 1) 2200 Series end drive conveyor with V-guide belt tracking, 16in (406mm) wide x 3.94ft (1201mm) long, drive shaft in position D with type 01 - low side profile on both sides and belt type 01, FDA Accumulation with fused finger splice. Configuration includes standard drive and idler tail and mounting brackets. Uncrated weight = 44lb (20kg).</p> <p>22MBES16D-2828 (Qty 1) 2200 Series Standard Load 90 Degree bottom mount package for a end drive conveyor, mounted in the D position, 28:28 pulley ratio. Uncrated weight = 6lb (3kg).</p> <p>62M060ES423EN (Qty 1) Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 29 RPM, providing a belt speed of 2 - 10 ft/min (0.6 - 3 m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).</p> <p>39MAH16-2436F (Qty 2) Adjustable Height Stand with fixed foot pads for a 16in (406mm) wide conveyor. Stand is adjustable from 24in (610mm) to 36in (914mm). Stand has a base width of 17.5in (444mm). Uncrated weight = 23lb (10kg). Required stand height is 25.8in (655mm).</p>	0%	3.593,00	1	25%	2.694,75
<p>PATN-0000538 - CNV 004 22EDM10-151020A050502 (Qty 1) 2200 Series end drive conveyor with V-guide belt tracking, 10in (254mm) wide x 15.10ft (4602mm) long, drive shaft in position A with type 05 - 1.5in (38mm) bolt-on aluminum high side profile on both sides and belt type 02, General Purpose with fused finger splice. Configuration includes standard drive and idler tail and mounting brackets. Uncrated weight = 92lb (42kg).</p> <p>22MBES10A-4432 (Qty 1) 2200 Series Standard Load 90 Degree bottom mount package for a end drive conveyor, mounted in the A position, 44:32 pulley ratio. Uncrated weight = 6lb (3kg).</p> <p>62M040ES423EN (Qty 1)</p>					

Standard load 90 Degree VFD Variable Speed gearmotor, .38 Hp (.28kw), 230/460 volt, 43 RPM, providing a belt speed of 3 - 21 ft/min (0.9 - 6.4 m/min). Order variable speed controller separately. Uncrated weight = 15lb (7kg).	0%	5.736,00	1	25%	4.302,00
39MAH12-2436F (Qty 3) Adjustable Height Stand with fixed foot pads for up to a 12in (305mm) wide conveyor. Stand is adjustable from 24in (610mm) to 36in (914mm). Stand has a base width of 13.5in (343mm). Uncrated weight = 23lb (10kg). Required stand height is 25.8in (655mm).					
39MB-TS (Qty 3) Diagonal bracing for H style stands up to 30in (762mm) tall.					
PATN-0000541 (Ref. producto proveedor 27M500-1603) - 2200 guia interior Lane guide kit with English documentation for a 2200 or 3200 series in 18in (457mm) wide x 3.00ft (914mm) long conveyor.	0%	418,00	1	25%	313,50
PATN-0000542 (Ref. producto proveedor 27M502-03) - 2200 guia interior adicional Additional lane kit with English documentation for a {3.00ft (914mm)} long conveyor	0%	241,00	1	25%	180,75

Condiciones de pago: Pago a 30 días

Tipo de pago: Transferencia bancaria

Total (Base imp). 13.668,00

Total IVA 0,00

Total 13.668,00